

WHITE



Available size



8"x40"*
 ± 0.35" / 9 mm
 * 7 3/4" x40" nominal size

Color shading



V3

GRAY



Available size



8"x40"*
 ± 0.35" / 9 mm
 * 7 3/4" x40" nominal size

Color shading



V3

The colour of tiles printed in this catalogue may differ from actual tiles. Tile color reproductions in this catalogue are representative only. Slight tone and shade variations are inherent in porcelain tiles. Before selecting a colour, we recommend that you contact your local representative, who will provide you with a sample piece of the requested tile.

ALMOND



Available size



8"x40"*
 ± 0.35" / 9 mm
 * 7 3/4" x40" nominal size

Color shading



V3

BROWN



Available size



8"x40"*
 ± 0.35" / 9 mm
 * 7 3/4" x40" nominal size

Color shading




V3

This porcelain tile product is manufactured with a V3 shade variation. Remember that the amount of colour as well as the texture of each piece may vary from tile to tile. Inspect the product immediately upon delivery and select tiles from many boxes during installation to minimize and blend any possible colour difference.

Color Shading



	COVE BASE
	 6" x 12"
WHITE	•
GRAY	•
ALMOND	•
BROWN	•

RECOMMENDED USE

Timeless is recommended for indoor floors, walls, countertops, and outdoor walls in commercial and residential application. The use of Timeless is not recommended for outdoor application or horizontal exterior surfaces. Landmark recommends an offset no greater than 30%, if a staggered pattern is required for tiles of 20" inches or longer.

CARE AND MAINTENANCE

Do not apply any wax or sealer to the product after installation. Regular cleaning is the best way to keep Timeless tiles looking good. Use clean, hot water (add household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth to prevent water spots. Please visit lcusa.com. For further information regarding the care and maintenance of Landmark products.

WARRANTY

Landmark guarantees that its products will meet or exceed the performance specifications set out in ANSI A137.1- 2012 and in the performance specifications section of the Landmark general catalogue. For more information, please visit our website at lcusa.com.

